



MINI-SAT STARTER PACKAGE

FEATURE

This MINI-SAT Starter Package allows the user to remotely monitor a well's water level from the comfort of the Internet. This starter package can be expanded to monitor the flow rate, total flow and salinity of the water being pumped. The pump can be controlled by the system using the optional control capability on the MINI-SAT Field Station.

MINI-SAT Field Station	Field Station with satellite capabilities. Includes: 4 analog input channels, satellite radio, whip antenna and battery.
LEVEL-WATCH	11' range water level sensor with 12' of vented cable
SOLCHGR-12-300	Solar Panel, 300mA, 12V, 15' of cable.
DESI-REPLACE	Prevents moisture from entering vent tube of Level-Watch. Includes 5' cable.
CABLE –VENTED	12' vented cable attached to LEVEL-WATCH sensor
COMMUNICATION	Annual communication charges for the MINI-SAT based on every 15 minute reporting.
WEB SERVER	Allows the user to log on to Automata's web site with an user ID and password to view and retrieve collected data.



MINI-SAT Field Station
(Some accessories not included)



LEVEL-WATCH



DESI-REPLACEMENT



SOLAR PANEL

Optional for MINI-SAT Field Station	
EC-WATCH	Water conductivity sensor with 25' cable.
VORTFLOW	Vortex insertion flow meter
FLOW COMP	Computes flow rate and totalized flow from above the VORTFLOW METER
MINI-OUT & IN	(1) control output and (1) Accumulator event input.

Domestic Prices shown are subject to change and do not include freight or sales tax. Computer not included. Please call for International Prices or for information on other configurations.

**Email: sales@automata-inc.com • <http://www.automata-inc.com>
Fax: (530) 478-5881 • Phone: (530) 478-5882 • (800) 994-0380
104 New Mohawk Rd., Suite A • Nevada City, California 95959**